

6,500 ANSI Lumens • XGA • 3LCD

LC-XN200L

"Conference" Series Projector



Cost-Effective, Large Venue Performance 3LCD projector with flexible installation including vertical and horizontal power lens shift and digital keystone correction.

Shown with standard lens (lens not included)



Key Features:

- △ 6,500 ANSI lumens bright with a 2000:1 contrast ratio.
- △ Native XGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- △ Supports analog and digital video input in all color standards up-to 1080p.
- △ 10-bit color processing, for superior color reproduction.
- △ Optional wide-angle and telephoto lenses.
- △ Vertical and Horizontal power lens shift and digital keystone correction.
- △ HDMI® input supports digital data, plus digital video with HDCP.
- △ Accepts composite, component, and S-Video in all major standards.
- △ Wired LAN connection for monitoring and control. Zigbee Control.
- △ Built-in Edge Blending. Wireless LAN.
- △ Crestron RoomView™ & AMX Device Discovery Compatibility.
- △ Centered lens with 1-button release. Top-accessed lamp, rear-accessed filter.
- △ Variable power management option. Optional local or remote keylock.
- △ Mechanical shutter for true black screen. Corner keystone correction.
- △ Picture-in-Picture & Picture-by-Picture. Wireless/wired remote control.
- △ 3 year projector warranty.



EIKI
Projectors... and more!



LC-XN200L SPECIFICATIONS:


Brightness	6,500 ANSI Lumens (with standard lens AH-24741)
Contrast Ratio	2,000:1
Resolution and Aspect Ratio	XGA (1024 x 768), 4:3
Color Reproduction	10-bit (1.07 billion colors)
Projection Lamp	350 Watts NHS
Estimated Lamp Life	up-to 4,000 hours
Total Pixels	2,359,296 (1024 x 768) x 3
Imaging System	0.79 in (20 mm) inorganic LCD Panels x 3
Scanning Frequency	Auto: H Sync. 15 ~ 100 kHz, V Sync. 48 ~ 85 Hz
Pixel Clock	150 MHz
Lens	Changeable - Power Zoom and Focus
Lens Specs	Speed: f : 1.7 ~ 2.3; FL: 1.06 ~ 1.78 in (26.9 ~ 45.4 mm)
Lens Ratios	Zoom Max:Min: 1.7:1; Throw:Width 1.7 ~ 2.89:1
Image Diagonal	40 ~ 300 in (101.6 ~ 762 cm)
Image Width	2.67 ~ 20 ft (0.81 ~ 8.1 m)
Throw Distance	4.6 ~ 58 ft (1.4 ~ 17.6 m)
Projector Elevation Adjustment (legs)	up-to 5° Up or Down
Maximum Pitch	up-to 360°
Vertical Lens Shift (% of image height)	up-to 50% Up or Down
Horizontal Lens Shift (% of image height)	up-to 10% Left or Right
Vertical Keystone Correction	Digital: up-to 30° Up or Down
Horizontal Keystone Correction	Digital: up-to 15° Left or Right
Image Orientation	Normal, Reversed, Inverted
Local Control / Power Management	Full Function / Auto Shutdown
Remote Control	Wireless/Wired (with laser pointer) x 1
Wired Remote Control	MiniStereo x 1
RS-232 Control	Dsub9 x 1
LAN Port	RJ45 x 1
Computer Input in Pixels	up-to 1600 x 1200 (4:3), 1920 x 1200 (16:10)
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, SVGA, VGA, MAC
Analog Wide Inputs	WUXGA, WSXGA, WXGA
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Digital Wide Inputs	WUXGA, WSXGA+, WSXGA, WXGA+, WXGA
Video Formats	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Video Input Analog	480i/p, 575i/p, 720p, 1035i, 1080i/p

Video Input Digital	480p, 575p, 720p, 1035i, 1080i/p
Image Signal Resizing	Smart Scaling Technology
Image Signal Inputs	
1. Analog Computer 1 & 2	Dsub15 x 2
Digital Video w/ HDCP	HDMI x 1
Digital Video w/ HDCP	DVI-D x 1
2. Analog Computer (RGBHV)	BNC x 5
Component Video	BNC x 3
Component Video	BNC x 1
S-Video	S-Video x 1
USB Display	USB Type B x 1
Wifi Display / Flash Drive	USB Type A x 1
Audio Signal Inputs	Stereo: MiniStereo x 1
Outputs	
Computer 2	Dsub15 x 1
Wired Remote Control	MiniStereo x 1
Amplifier	Mono: 7 Watt
Fan Noise	as low as 32 dBA
Cabinet Size (HxWxD)	7.5 x 21 x 18.3 in (19 x 53.4 x 46.4 cm) (with standard lens AH-24741)
Weight	(without lens) 21.3 lb (9.69 kg)
Packaged Size (HxWxD)	13.5 x 24.5 x 26.5 in (34.2 x 62.2 x 67.3 cm)
Packaged Weight	(without lens) 33.2 lb (15.09 kg)
Operating Temperature	41 ~ 95°F (5 ~ 35°C)
Electrical Safety Compliance	IEC / UL / cUL
Electromagnetic Compatibility	FCC Class B, CE Mark
Power Requirements	100 ~ 240V AC, 50/60 Hz
Power Consumption	0.5 W in Eco Standby mode, up-to 480 W
Heat	up to 955 BTU / hr.
Security Facilities	Kensington® Security Slot
UPC	4571194676907
User Maintenance	Clean Filter, Replace Lamp
Limited Warranty: to the original end-use customer only	
Projector	*3 years / 6000 hours
Lamp	*6 month ownership / 500 hours use *(which ever occurs first)

EIKI® is a registered trademark of EIKI International, Inc. Kensington® is a registered trademark of ACCO Brands Corporation.
HDMI® is a registered trademark of HDMI Licensing LLC. Crestron Roomview™ is a registered trademark of Crestron Electronics, Inc.



Includes a full complement of connections, including network control.



LC-XN200L • XGA projector.



Handy access to air filter.



Easy to change long-life lamp.



Wireless adapter.

INCLUDED ACCESSORIES:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 10 ft (3 m) Detachable Power Cord, Wireless Remote Control (with 2 AA Batteries), USB Wifi Dongle, USB Zigbee Dongle, Rubber Lens Cover, Zigbee Antenna, Rubber Gasket.

OPTIONAL ACCESSORIES:

Replacement Lamp, Wideangle, Midrange and Telephoto Lenses, ATA-Style Shipping Case with Wheel and Telescoping Handle, Ceiling Mount, Ceiling Post and Plate.

Specifications subject to change without notice. ©2014 EIKI International, Inc. Printed in the USA. 12/15/14



EIKI International, Inc.

30251 Esperanza Δ Rancho Santa Margarita, CA 92688-2130
Phone: 800-242-3454 Δ Fax: 800-457-3454 Δ E-mail: usa@eiki.com

In Canada: 310 First St.- Unit 2, P.O. Box 156 Δ Midland, ON L4R 4K8
Phone: 800-563-3454 Δ Fax: 800-567-4069 Δ E-mail: canada@eiki.com